



H4 Handheld

Secure Mobility HMI in your Hand





...Our Word Counts



H4 Handheld

Key Features

Certified Wireless Safety SIL2

JMobile Integrated

Easy to Program

Stunning Design/Ergonomics

Multiple Integrated Keys

Potentiometers

Handwheel

State Selector

Bluetooth Safety

Additional WiFi Connectivity

Magnets to Hang Devices in
Convenient place

Up to 50 m Connection

The H4 Handheld device is a true HMI in your hand: powerful and easy to program to your needs it remains the perfect choice for safe mobile requirements.

The wireless option leads to many positive features being enhanced:

- Higher Safety in all areas with no pendant wires to causes issues
- Less injury risks
- No broken cable downtime
- Far less physical fatigue of operator
- Increased concentration of operator

The wireless connection is provided by a Unique electronic key which allows for multiple handheld – machine connections to take place simultaneously without any concern for connectivity and of course safety.



Data Sheet



H4 Handheld - Technical Data



System Resources	
Display - Colors	TFT LED - 64K
Resolution	480x272, WQVGA
Brightness	300 Cd/m ² typ.
Dimming	to 0%
Touchscreen	Resistive
CPU	ARM Cortex-A8 - 600 MHz
Operating System	Microsoft Windows CE 6.0
Flash	128 MB
RAM	256 MB
Real Time Clock, RTC Back-up	Yes
Handwheel	Yes
Potentiometer	2
State Selector Switch	16 positions
Emergency stop	Yes
Enabling Switch	3 positions
Interface	
Ethernet	Wi-Fi 802.11
USB port	1 Host V2.0
Bluetooth	Reserved for safety functions
Ratings	
Power supply (charging station)	24 Vdc (18 to 30 Vdc)
Current Consumption	0.25 A at 24 Vdc (max.)
Input Protection	Automatic
Battery	Rechargeable Lithium battery, not user-replaceable
Environment Conditions	
Operating Temp	+5 to +45°C
Storage Temp	-20 to +70°C
Operating / Storage Humidity	5-85% RH, non condensing
Protection Class	IP64
Dimensions and Weights	
Faceplate LxH	220x144 mm
Depth D	63 mm
Weight	Approx 0.8 Kg
Approvals	
CE	Emission EN 61000-6-4 Immunity EN 61000-6-2 for installation in industrial environments
Safety	2006/42/EC, EN ISO 13849-1:2008, EN 62061 :2005/A1:2013, EN 60204-1:2006/A1:2009
Safety functions	Emergency Stop cat 3, PL d / SIL 2 Enabling cat 3, PL d / SIL 2 State selector, cat 1, PL c / SIL 1



EXOR



U.S.A.

Exor America
Tel.: +1 513 874 0900
Fax: +1 513 874 2707
info.us@exorint.com

GERMANY

Exor Deutschland GmbH
Tel.: +49 202 27911 0
Fax: +49 202 27911 44
info.de@exorint.com

ITALY

Exor International S.p.A.
Tel.: +39 045 8750404
Fax: +39 045 8779023
info.it@exorint.com

SWITZERLAND

Exor Schweiz GmbH
Tel.: +41 55 6195807
Fax: +41 55 6195806
info.ch@exorint.com

INDIA

Exor India Private Ltd.
Tel.: +91 022 27810422
Fax: +91 022 27810424
info.in@exorint.com



IIoT industry 4.0 ready



PLATFORM